

概述 Overview

机座号: 80 ~ 280

额定电压: 380 V

额定频率: 50 Hz

冷却方式: IC411

防护等级: IP54

绝缘等级: F 级

环境温度: -15 ~ 40 °C

海拔高度: 不超过 1000 m

Frame size: 80 ~ 280

Rated voltage: 380 V

Rated frequency: 50 Hz

Cooling method: IC411

Protection degree: IP54

Insulation class: F


Coolant temperature: -15 ~ 40 °C

Site altitude: Up to 1000 m above sea level

YD 系列变极多速三相异步电动机，适用于需要逐级调速的各种传动机构。

YD series pole-changing multi-speed three-phase asynchronous motors can apply to various transmission mechanism which need control speed step by step.

订货号 Order No.



电机系列 Motor series

机座号编号 Code of frame size

80 / 90 / 100 / 112 / 132 / 160 / 180 / 200 / 225 / 250 / 280

机座长度编号 Code of frame size

S = 短机座 M = 中机座 L = 长机座

注：机座长度编号后面的数字代表同一机座号和转速下的不同功率。

Note: The numbers after the code of frame length represent different power in the same frame size and same speed

极数编号 Code of poles

4/2 6/4 8/4 12/6

功率 Rate Output kW

机座安装方式 Code of mounting type

B3 = IM B3

B5 = IM B5

B35 = IM B35

接线盒的出线方向 (从驱动端看) Code of connection box location (view from drive end)

K09 = 右侧 on RHS

K10 = 左侧 on LHS

K11 = 置顶 on top